

## AddSecure Asset installation protocol

<b>Customer name</b>				
<b>GSM data no. of the sim-card</b>				
<b>Serial no. of the Asset unit</b> (to be found beneath the barcode)				
<b>Date of installation</b>				
<b>Location of unit</b>				
<b>Name of technician</b>				
<b>Registration no. or vehicle name</b>				
<b>Ignition wire is connected to:</b> (mark with X)	Ignition		+12/+24 Volt DC	
<b>If connection to a <u>data logger</u> of a cooling machine:</b>  Which make, model and connection variant (fx. Thermo King CoolerLog DAS serial-RS232 or Thermo King iBox CAN-Bus)				
<b>If connection to One-wire temperature sensors:</b>  Serial no. and name/location of the temperature sensor(s)				
<b>If connection to Wireless temperature sensors:</b>  Serial no. and name/location of the temperature sensor(s)				

This installation protocol must be filled in, send to AddSecure Support ASAP (e-mail to [support.smarttransport@addsecure.com](mailto:support.smarttransport@addsecure.com)) AND given to the customer's Co-Driver Weboffice administrator.

The data provided in the installation protocol must be available in order to a correct Co-Driver Weboffice configuration can be made, and for any later contact to AddSecure Support.

**The device will only be visible on Co-Driver Weboffice after successful mandatory final test (STAT-SMS).**

In case of questions contact AddSecure support  
 AddSecure support phone no.: +46 31 77 92 979  
 E-mail: [support.smarttransport@addsecure.com](mailto:support.smarttransport@addsecure.com)